OUR M¥ST SPACE EFFICIENT HOÄE LIFT

Aritco HomeLift Compact

Sometimes great things come in small packages. Our most spaceefficient lift, the Aritco HomeLift Compact, opens up a world of possibilities in homes that were previously considered too limited in space for a lift. With its modern design, customizable features, and connectivity, the home lift offers the advantages of being small combined with the ability to think big.

Aritco HomeLift Compact offers you an unique Aritco Scandinavian design; a sleek platform design, a DesignWall and control panel with integrated handrail, double doors and contemporary and flexible shaft glass solutions. Accessible online via Aritco SmartLift.















Explore Aritco HomeLift Compact	
Key features	The lift also serve you several customization possibilities. You can choose from more than 200 different colors, 2 different glass types, 8 different floorings and a DesignWall (backwall) with 8 different artworks. The lift is SmartLift enabled which means you also get live status information in the app and the maintenance provider can get access to a Fleet management system for remote monitoring and support of the lift. The lift is also equipped with our SmartSafety system, with safety features, to meet all situations that can occur in a home, to prevent accidents.
Sizes	MODEL CARRIER SIZE (AxB) EXTERIOR DIMENSIONS (CxD) RATED LOAD 1 580 x 805 mm 840 x 880 mm 250 kg / 2 persons 2 880 x 805 mm 1140 x 880 mm 250 kg / 2 persons 3 1080 x 805 mm 1340 x 880 mm 250 kg / 2 persons
DesignWall	
Lift color	Comes in three standard colors, Traffic White (RAL9016), Jet Black (RAL 9005) and Anthracite Grey (RAL7016). Can be painted in any RAL color from the RAL K7 classic chart (Except for pearl and fluorescent colors)
Glass	STANDARD Clear glass OPTIONAL Tinted
Floor	Conc credi Conce do C
Intended use	Home lift intended for transportation of persons in buildings where the users are known. Indoor installation environments
Technical compliance	European Machine Directive 2006/42/EC European Standard EN 81-41
Drive system	Patented screw-and-nut system
Rated speed	Max 0.15 m/s
Emergency lowering	Battery-powered
Travel height	1 600 - 15 000 mm
Top height	Always 2 248 mm
Number of floors	2 to 6 floors
Installation	Recessed installation 50 mm below floor level Installed directly on floor with 50 mm ramp
Operation	Hold to run (press and hold) One-touch operation (press one time) for installations outside Europe
Power supply	230 V 1-phase
Warranty	Aritco HomeLift Compact comes with a 5-year product warranty and a 10-year drive technology warranty.5

ARITCO LIFT 2025 FEB - EN